



Technical Data Of Magnetic Roller

NO.	Model	Magnetic induction intensity of the drum surface (GS)	Material depth (≤mm)	Belt speed (m/s)	Weight (kg)	Appearance size (mm)								
						A	B	DΦ	L	L1	K	dΦ	h	b
1	RCT-32/40	1500-3000	40	≤2.5	150	728	400	320	500	926	100	45	48.5	14
2	RCT-32/50	1500-3000	60		198	850	500	320	600	1097	115	50	53.5	14
3	RCT-40/50	1500-3000	80		250	850	500	400	600	1097	115	55	60	16
4	RCT-50/50	1500-3000	100		370	850	500	500	600	1097	115	55	60	16
5	RCT-32/65	1500-3000	70		245	1000	650	320	750	1280	135	65	69	18
6	RCT-40/65	1500-3000	100		405	1000	650	400	750	1280	135	65	69	18
7	RCT-50/65	1500-6000	130		520	1000	650	500	750	1280	135	70	76	20
8	RCT-50/80	1500-6000	130		610	1300	800	500	950	1580	135	70	76	20
9	RCT-65/80	1500-6000	130		720	1300	800	650	950	1661	175	70	76	20
10	RCT-80/80	1500-6000	150		980	1300	800	800	950	1661	175	90	76	24
11	RCT-65/100	1500-6000	130		910	1500	1000	650	1150	1861	175	90	97	24
12	RCT-80/100	1500-6000	170		1200	1500	1000	800	1150	1954	215	90	97	24
13	RCT-65/120	1500-6000	100		1500	1750	1200	650	1400	2194	215	110	119	32
14	RCT-100/120	1500-6000	200		1890	1750	1200	1000	1400	2270	255	110	119	32
15	RCT-100/140	1500-6000	230		2160	2000	1400	1000	1600	2446	255	110	119	32
16	RCT-125/160	1500-6000	260		2800	2150	1600	1250	1800	2600	255	120	129	32

Note: The strength of the magnetic field can be customized according to customer requirements, from 800gs-10000gs, please indicate in the contract.